# **Builder Series**

# Wet Location Polycarbonate Exit Series BPW

REV #: 09.21.02

#### **ILLUMINATION**

- Ultra bright, energy efficient LED emergency lighting.
- Long life, energy efficent Red or Green LED Exit sign illumination

# **ELECTRICAL**

# **AC Operation**

- Universal Input 120/277VAC
- Long life, maintenance-free, rechargeable NiCd battery.
- Remote capacity of 3.0 watts standard
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

#### DC Operation

- 24VDC for Central Storage Battery systems.
- 60VDC for POE or DC power distribution systems.

#### MOUNTING

- Polycarbonate mounting canopy included for top or end mount
- Universal knockout pattern on back plate for wall mount.

### **HOUSING**

- Injection-molded, 5VA flame retardant, high-impact resistant, thermoplastic in white, gray, or black finish.
- Low-profile, universal Single/Double Face
- EZ snap-out Chevron directional indicators.
- Adjustable Down Light

### **OPTIONS**

- Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes
- Custom Lettering = Signs available with requested "special" wording
- DC Operation

# WARRANTY/LISTING


- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 50°C).
- Certified to CED under Title 20 Regulations



TYPE:

CATALOG #:





# STANDARD:















# FIXTURE ORDERING INFORMATION EXAMPLE: BPW-BB-1-R-W-DG

BPW

SERIES	OPERATION		# OF FACES		LETTER COLOR		HOUSING COLOR		OPTIONS	
	ВВ	120/277VAC with Battery	1	Single	R	Red	W	White	DG	Self-Test Diagnostics <sup>1</sup>
BPW	NB	AC only	2	Double	G	Green		(with white faceplate)	TP	Tamper Proof
	REC	Central Battery					В	Black	48	48VDC input <sup>2</sup>
								(with black faceplate)	60	60VDC input <sup>2</sup>
							G	Gray	2C	Dual Circuit Operation <sup>3</sup>
								(with white faceplate)	CUSTOM	Custom Wording



<sup>1</sup>BB models <sup>2</sup>REC models <sup>3</sup>Available only with NB units Special voltage & SALIDA face plate options available. Contact Signtex for more information.